

A4 Annunciation Panel

Douglas A-4N Skyhawk Annunciation Panel



WirelessKable Inc.

Proudly Made in CANADA with domestic and imported parts

Document Revision: A

SPECIFICATIONS

Input Voltage	9 – 32 VDC 7.5 – 28VAC (400Hz) – Dimming purpose only
Input Current	0.022A @ 28VDC 0.135A @ 28VDC (All Signs ON)
Weight	0.68 lb (330 g)
Dimensions	Faceplate 1.25" W / 4.06" L / 0.04" H Product 1.25" W / 4.9" L / 4.4" H
Inputs	11 GND Active Inputs 4 28VDC Active Inputs
Outputs	1 Open Collector Output (with timer) 1 28VDC Output (relay driver with protection)
Mounting	Back with 4 Screw 6/32
Certification	RTCA DO-160G
Applications	A-4N Skyhawk Aircraft
Appearance	Hard Black Anodized
Protections	Input overvoltage, Discrete Inputs, Discrete Outputs
MTBF	300,000 Hours

ORDERING INFORMATION

Part Number	A-31001-1
Description	A4 Annunciation Panel (LH)
Part Number	A-31001-5
Description	A4 Annunciation Panel (RH)



DESCRIPTION

Designed as a “form fit function” replacement for the original annunciation panel of Douglas A-4N Skyhawk

FEATURES

- All signs can be customized for different missions
- Customizable functionality
- Very High Reliability
- Very Low Power Consumption
- Reduced Weight (half of the original part)
- LED Redundancy - 4 (four) LEDs per row with Zenner diode protection