

# USB-C Faceplate X

USB Type C Faceplate



WirelessKable Inc.

Proudly Made in CANADA with domestic and imported parts

Document Revision: A

## SPECIFICATIONS

|                       |  |
|-----------------------|--|
| <b>Input Voltage</b>  | USB-C PD with Data Passthrough   |
| <b>Input Current</b>  | 5.0 A Max  |
| <b>Output Voltage</b> | USB-C PD with Data Passthrough   |
| <b>Output Current</b> | 5.0 A Max  |
| <b>USB Connector</b>  | Secure USB type C to USB-C   |
| <b>Weight</b>         | 0.055 lb (25 g)  |
| <b>Dimensions</b>     | Faceplate 1.12" W / 1.12" L / 0.75" H<br>Cut-out 1" W / 1" L<br>Product 1.12" W / 1.12" L / 0.97" H  |
| <b>Mounting</b>       | Front with Spring Clips  |
| <b>Certification</b>  | RTCA DO-160G<br>Compliance with EN50155<br>Design as per USB PD rev 2.0  |
| <b>Applications</b>   | Aerospace, Railways, Automotive, Military  |
| <b>Appearance</b>     | Standard - Gray Anodized<br>Optional plating on demand   |
| <b>Used With</b>      | 551-5117-001 - USB-C DC100FM<br>551-5307-001 - USB-C AC100 Mode 1<br>551-5307-003 - USB-C AC100 Mode 3<br>551-5407-001 - USB-C Cable<br>551-5607-001 - USB-C to HDMI Converter |
| <b>Mating Cycles</b>  | 50,000   |

## ORDERING INFORMATION

|                    |                   |
|--------------------|-------------------|
| <b>Part Number</b> | 551-5507-001      |
| <b>Description</b> | USB-C Faceplate X |



## DESCRIPTION

The product is a USB-C pass-through passive device. Is used as a small footprint USB-C external connector when used with USB-C Converters or in conjunction with USB-C to HDMI Converter.

The faceplate can be plated for special needs.

## FEATURES

- A very small footprint
- Lightweight
- Platable Faceplate
- Cost-effective solution